

*Color Stop Thread Sheet***Peacock Bracelet***by Laura Doyle***Note: Disregard black dot on this scan.**

Design # **Sizes**
 #4337 16 ct 45 x 239mm (1.77 x 9.39")
 #4338 18 ct 42 x 223mm (1.65 x 8.76")
 Total Stitches - 36,577

Suggestions for Metallics: Use metallic threads whenever possible. Check in your local shop for **Superior Metallics #7, N56,N24,N28,N27,N30 and N38.** We also suggest trying **Madiera Copper and Yenmet Metallics.**

Stop #	DMC Color Name	Stitch Part	Cotton	Cotton	Rayon	Rayon	Rayon	Polyester
			50wt DMC	60wt Mettler	40wt Sulky	40wt Rob/Ant	40wt Madeira	40wt Isacord
1	Black**	centers	310	3	1005	2296	1074	20
2	Metallic Royal Blue	centers			7016			
3	Metallic Emerald	centers,feathers		5833	7018			
4	Metallic Turquoise	centers		4101	7015			
5	Metallic Copper	centers,feathers			7011		9842	
6	Chartreuse Bright	centers	704	903	1332	2321	1074	5610
7	Pistachio Grn Medium	feathers	320	549	1276	2278	1098	5101
8	Pistachio Grn Very Dk	feathers	319	850	1174	2392	1028	5555
9	Metallic Forest Green	centers			7056			
10	Metallic Gold	border			7007			
11	Metallic Copper	backstitch feathers			7011		9842	

****NOTE: Stop #1 is optional when stitching on black fabric. Skip stop #1 only if stitching on black fabric!**

Illustrated to right:

Right: Bracelet with design #4338.

Note: Instructions for bracelet assembly on page 25.

Models stitched with DMC 50wt cotton and Sulky Metallics.

©2004 Sudberry House LLC. All rights reserved



**Machine Cross Stitch
Embroidery**

www.machinecrossstitch.com



Watchband Assembly Instructions

1. After stitching is complete, trim 3/8" around three sides. Then cut into where stitching ends at a right angle and extend the watch slot fabric 1 1/4" the same width as the stitching. Fray check around this as it will be the raw edge you will be working with to attach band to the watch. Fray check bottom short end also.
2. Cut four pieces of 3/8" black grosgrain ribbon into 4" lengths. Press over ends on the short sides.
3. "Hook" folded edge of ribbon over top raw edge and top stitch (machine or hand) ribbon on both long sides close to the metallic edge.
4. Press bottom raw edge up and grosgrain ribbon sides together. Unwrap watch face. With tweezers, pull the unstitched fabric through the slot so the stitching meets the face. Fold down and hand stitch firmly to the wrong side of the stitching. Now hand stitch ribbon sides together from end to center of the band up to the watch slot. On the pointed end, miter the stitched fabric only-the ribbon should be straight across below the miter. Folding under of the grosgrain on both ends requires patience!
5. Handle the watch carefully to avoid battery malfunction. To start the battery press in watch face stem.
6. Stitch sew on snaps to each end positioning to the size of your wrist. (or sew on tiny Velcro dots)



Bracelet Assembly Instructions

1. After stitching is complete, trim within 1/4" of stitching. Press raw edges toward wrong side.
2. Cut a piece of ultra suede using the finished stitching as a pattern. With fine stitches hand sew ultra suede to bracelet.
3. Add snaps, Velcro tabs, or hook & eye to wrist size desired. Add decorative button to top tab if desired.